
SL40-60MBI
350~365W

HALF-CUT Series

1,000V Monocrystalline PV Module

All Black



CERTIFICATIONS

IEC 61215, 61730 / UL 61730
ISO 9001 : Quality Management System
ISO 14001 : Environmental Management System
ISO 45001 : Occupational Health & Safety System

FEATURES

Enhanced External Load/Impact
Snow Load : 5,400 Pa
Wind Load : 2,400 Pa

PID Resistance
Enhanced Potential Induced Degradation Resistance


Fire Safety
Spread of Flame Class A
Burning Brand Class C

Higher output power
0~+5Wp,
Higher than rated power

Excellent performance under low light conditions
Cloudy days, mornings and evenings

WARRANTY

12 -YEARS PRODUCT WARRANTY
25 -YEARS LINEAR PERFORMANCE WARRANTY



S-Energy Co., Ltd.
A 20 PanGyoYeok-Ro 241BeonGil, BunDang-Gu, SeongNam-Si, GyeongGi-Do, Korea (3F MiraeAsset Tower)
T +82-70-4339-7100 F +82-70-4339-7199 E inquiry@s-energy.com

S-Energy America (SEAI America, Inc.)
A 18022 Cowan, Suite 260, Irvine, CA 92614, U.S.A.
T +1-949-281-7897 F +1-949-281-7893 E sales.us@s-energy.com

S-Energy Chile (S-Energy Chile SpA)
A Av. Cerro El Plomo Nº5420, Office 402, Las Condes, Santiago, Chile
T +56-22-604-8111 E sales.cl@s-energy.com

S-Energy Japan_Osaka Headquarters (S-Energy Japan Co., Ltd.)
A 8F, MJ Abeno Bldg., 1-5-1, Maruyama-dori, Abeono-ku, Osaka-shi, Osaka, Japan
T +81-6-4703-5388 F +81-6-4703-5387 E sales_jp@s-energy.com

S-Energy Japan_Tokyo Branch (S-Energy Japan Co., Ltd.)
A Fukuroku Building 2F, 2-7 Kanda-Tsukasamachi, Chiyoda-ku, Tokyo, Japan
T +81-3-6261-3759 F +81-3-6261-3769 E sales_jp@s-energy.com

Homepage

SL40-60MBI

1,000V Monocrystalline PV Module 350W · 355W · 360W · 365W


S-Energy

ELECTRICAL CHARACTERISTICS

STC (Irradiance 1,000W/m², module temperature 25℃, AM=1.5)	SL40-60MBI-350V	SL40-60MBI-355V	SL40-60MBI-360V	SL40-60MBI-365V
Rated Power (Pmax)	350W	355W	360W	365W
Voltage at Pmax (Vmp)	33.6V	33.8V	34.0V	34.2V
Current at Pmax (Imp)	10.42A	10.51A	10.59A	10.68A
Warranted Minimum Pmax	350W	355W	360W	365W
Short-Circuit Current (Isc)	11.19A	11.26A	11.35A	11.43A
Open-Circuit Voltage (Voc)	40.1V	40.3V	40.5V	40.7V
Module Efficiency	18.95%	19.22%	19.50%	19.77%
Operating Module Temperature	-40℃ to + 85℃			
Maximum System Voltage	1,000V			
Fuse Rating	20A			
Maximum Reverse Current	27A			
Power Tolerance	0 ~ +5W			


MECHANICAL CHARACTERISTICS

Solar Cells	Monocrystalline Cells 166x83mm
Number of Cells	60 Half Cells (6x20 Matrix)
Dimensions	1,762 x 1,048 x 35mm
Front Load	5,400Pa
Rear Load	2,400Pa
Weight	19.6kg
Glass	3.2mm High-Transmittance Low Iron Tempered Glass
Frame	Anodized Aluminum Frame (Black)
J-Box	≥ IP67 with 3 bypass diodes
Output Cables	PV Wire (PV1-F), 12AWG (4mm²), Cable Length : 500mm
Connectors	MC4 Compatible



TEMPERATURE CHARACTERISTICS

Temperature coefficient of Isc	0.048 % / ℃
Temperature coefficient of Voc	-0.270 % / ℃
Temperature coefficient of power	-0.350 % / ℃
NOCT (Tair 20℃ ; Irradiance 800W/m² ; Wind 1m/s)	45±2 ℃



PACKING CONFIGURATION

Container	20'	40'
Modules Per Pallet	30pcs	30pcs
Pallets Per Container	6pallets	26pallet
Modules Per Container	180pcs	780pcs

REMARKS

- Pmax measurement tolerance : ±2.5%
- S-Energy uses triple A class simulator.
- Specification subject to change without prior notice.
- S-Energy reserves the rights of final interpretation.

NOTES

Installation instruction supplied with the module must be duly followed. For further information which is not mentioned on installation guides or directions, please contact to our technical service department.

- E-mail : Inquiry@s-energy.com